




Image only for reference

CAB-T25-BG

- Suitable for Telephony Communication
- 25 Pair – Wired together with varying lays
- 24AWG Solid Bare Copper Conductors
- PE Tape, Rip Cord
- ETL CMR Verified, RoHS Compliant



Construction & Material:

Item	Specification	Construction
Product	CAT 3	Annealed Copper Conductor (24AWG), polyethylene insulation, units of 25 pairs Core: Tape(s) applied longitudinally Rip cord, LSZH outer sheath
Construction	1x25Pr	
External Diameter	10.7 mm (aprox.)	
Weight	165 kg/km (aprox.)	
Conductor Resistance	89.5 Ω /km	
Lenght	1000 ft	

Transmission		
Frequency (MHz)	Attn max. (dB/100m)	PS-NEXT min. (dB)
0.772	2.2	43
1	2.6	41
4	5.6	32
8	8.5	27
10	9.7	26
16	13.1	23

Colors Codes		
Number of Pairs	Conductor "a"	Conductor "b"
1	White	Blue
2	White	Orange
3	White	Green
4	White	Brown
5	White	Gray
6	Red	Blue
7	Red	Orange
8	Red	Green
9	Red	Brown
10	Red	Gray
11	Black	Blue
12	Black	Orange
13	Black	Green
14	Black	Brown
15	Black	Gray
16	Yellow	Blue
17	Yellow	Orange
18	Yellow	Green
19	Yellow	Brown
20	Yellow	Gray
21	Violet	Blue
22	Violet	Orange
23	Violet	Green
24	Violet	Brown
25	Violet	Gray

