



PCU-60XM-XX

- RoHS TYPE CM 60° C 24 AWG CSA LL81295
- CMG 60° C FT4 ETL VERIFIED
- TIA/EIA-568-B.2-1 CAT. 6 UTP 350MHZ
- GIGABIT READY www.tekdatasa.com
- TIA 568B
- TEKDATA+BATCH NO. +METER MARKING (BY FT)



Construction & Material:

	Item	Unit	Specification
Conductor	Product	-	CAT. 6 UTP 4P
	Size	AWG	24
	Number	P	4
	Material	-	Solid Bare Copper Wire
	Construction	pcs / mm	1 / 0.58 ± 0.005
	Diameter	mm	0.58
Insulation	Material	-	HD-PE
	Min.thickness	mm	0.176
	Avg. thickness	mm	0.198
	Diameter	mm	0.98 ± 0.02
	Color	-	Blue x White/Blue Orange x White/Orange Green x White/Green Brown x White/Brown
Twisting	Construction	-	See Cross - Section
Divider	Material	-	PE
Cabling	Construction	-	See Cross - Section
Ripcord	Ripcord	-	1500 DNYlon Rope
Jacket	Material	-	PVC
	Min. thickness	mm	0.38
	Avg. thickness	mm	0.49
	Overall Diameter	mm	6.2 ± 0.2
	Color	-	Yellow, Red, White, Blue, Gray
	Frequency	-	350 Mhz
	Lenght	ft	1 - 3 - 7