




Image only for reference

## PCU-6AXX-XX

RoHS TYPE CM 60° C 24 AWG CSA LL81295  
CMG 60° C FT4 ETL VERIFIED  
TIA/EIA-568-B.2-1 CAT. 6A UTP 350MHZ  
GIGABIT READY [www.tekdatasa.com](http://www.tekdatasa.com)  
TIA 568B  
TEKDATA+BATCH NO. +METER MARKING  
(BY FT)



### Construction & Material:

	Item	Unit	Specification
<b>Conductor</b>	Product	-	CAT. 6A UTP 4P
	Size	AWG	24
	Number	P	4
	Material	-	Solid Bare Copper Wire
	Construction	pcs / mm	1 / 0.58 ± 0.005
	Diameter	mm	0.58
<b>Insulation</b>	Material	-	HD-PE
	Min.thickness	mm	0.176
	Avg. thickness	mm	0.198
	Diameter	mm	0.98 ± 0.02
	Color	-	Blue x White/Blue    Orange x White/Orange Green x White/Green    Brown x White/Brown
<b>Twisting</b>	Construction	-	See Cross - Section
<b>Divider</b>	Material	-	PE
<b>Cabling</b>	Construction	-	See Cross - Section
<b>Ripcord</b>	Ripcord	-	1500 DNYlon Rope
<b>Jacket</b>	Material	-	PVC
	Min. thickness	mm	0.38
	Avg. thickness	mm	0.49
	Overall Diameter	mm	6.2 ± 0.2
	Color	-	Yellow, Red, White, Blue, Gray
	Frequency	-	350 Mhz
	Lenght	ft	1 - 3 - 7