




## PATCH PANELS CAT 5E

This category 5E patch panel is designed for high-density installations. Exceeds ANSI/TIA/EIA-568 C.2 standards, allows connections with conductors 22-26 gauge on the American scale (AWG).



### Construction & Material:

| No. | Item                    | PPC-245EP-R   | PPC-485EP-R   |
|-----|-------------------------|---|---|
| 1   | No. of ports            | 24  | 48  |
| 2   | Front panel             | 1.5 mm wide SPCC                                    | 1.5 mm wide SPCC                                    |
| 3   | Panel color             | Black Enamel (RAL 9005)                             | Black Enamel (RAL 9005)                             |
| 4   | Rack units              | 1U  | 2U  |
| 5   | Operating temperature   | -10°C to 60°C (ISO/IEC 11801, ANSI/TIA/EIA-568-C.2) | -10°C to 60°C (ISO/IEC 11801, ANSI/TIA/EIA-568-C.2) |
| 6   | Height                  | 44.4 mm   | 88.9 mm   |
| 7   | External Thickness      | 488.2 mm  | 488.2 mm  |
| 8   | Depth                   | 45 mm   | 45 mm   |
| 9   | Nominal Voltage         | 300 V   | 300 V   |
| 10  | Rated Temperature       | 75°C  | 75°C  |
| 11  | Transmission Speed      | 100 Mbps  | 100 Mbps  |
| 12  | Bandwidth               | 100 MHz   | 100 MHz   |
| 13  | International Standards | ANSI/TIA/EIA-568-C.2, ISO/IEC 11801                 | ANSI/TIA/EIA-568-C.2, ISO/IEC 11801                 |